

CBD15-170J

Electric Walkie Pallet Truck

Advantages

Configuration and Performance

- The truck has compact structure and is economic.
- Permanent magnet drive motor assembled on the truck has simple structure and is easy for maintenance.
- Stepless speed regulating is easy for operation and maintenance.
- Open type layout of battery is easy for replacement.
- Built-in charger is standard configuration.
- Maintenance-free battery is safe and non-pollution.
- The truck is compact and suitable for narrow space operation.
- Special design for Fork in and out of double-faced pallet.
- Lifting automatic limit is safe and energy saving.
- Emergency reversing device and emergency brake switch are standard configuration.
- The truck has low noise and small energy consumption and only 2 kw/h energy is consumed daily.



Feature			
Model			CBD15
Configuration No.			170J
Weight			1500
Load center	kg		600
Wheel base	mm		1285/1235
Operating type	mm		Walkie
Wheels			
Wheels type			PU
Wheel quantity			1/0/4
Driving wheel/Balance wheel /Bearing wheel			φ210×70
Driving wheel size	mm		φ84×70 (双)
Balance wheel size	mm		φ80×101 (单)
Bearing wheel size	mm		—
Dimension			
Min.fork lowered height	mm		85
Max.fork lifting height	mm		205
Max.lifting height	mm		120
Outside width between forks	mm		550/685
Inside width between forks	mm		390
Fork length	mm		1150/1200
Fork width	mm		160
Fork thickness	mm		73
Overall length	mm		1648/1698
Overall width	mm		570/685
Overall height(With handle)	mm		1213
Overall height(Without handle)	mm		634
Min.Turning radius	mm		1414/1464
Min.Aisle width for pallets 800×1200	mm		1728/1778
Min.Aisle width for pallets 1000×1200	mm		1764/1814
Performance			
Travel speed,laden/unladen	km/h		3.5/4
Lift speed,laden/unladen	mm/s		30/35
Lowering speed,laden/unladen	mm/s		35/30
Gradeability,laden/unladen	%		5/7
Electrical configuration			
Drive motor	KW		DC0.65
Lift motor	KW		DC0.8
Steering motor	KW		—
Battery voltage / capacity	V/Ah		24/75(Standard)/85(Options)
Brake			Electromagnetic/regenerative
Controller			Standard configuration HELI/Optional configuration CURTIS 1212F
Weight			
Battery weight	kg		50
Service weight with battery	kg		210

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI CO., LTD.

ADD: NO.668 Fangxing Street,Economical Development Zone,Hefei,P.R.China
TEL : 63639068(America); 63639258(Europe); 63639358(Asia); 63662105(Africa & Middle East);
63639530(Warehouse Equipment); 63639531(Wheel loader)
FAX : (86 551)63639966
WEBSITE : <http://www.helichina.net>
Email : hel@helichina.net

AUTHORIZED DEALER