

# CDD10-070

## 1.0 Ton Electric Fork Over Stacker

Lifting Height: 2000-3300mm

### Load Curve



### Advantages

#### Configuration and Performance

- Separately excited motor, Strong climbing ability.
- High strength forks.
- Built-in charger.
- Automatic lifting limit, Motor and battery life extension.

#### Safety

- Stepless speed control system, safe and quiet.
- Controller with Multiple automatic protection
- Emergency reversing device/Emergency brake switch.

**Built-in charger**

**Free-maintained battery**

**Integrated fork, much stronger**

**24 YEARS** TOP1 FORKLIFT MANUFACTURER AND SALER  
IN CHINA FOR CONSECUTIVE 24 YEARS

Type	Lift height (mm)	Mast type	Outside width between legs (mm)	Inside width between legs (mm)
CDD10-070	2000/2500/3000/3300	Standard 2-STAGE	550/600/650/685	180/230/280/315

# HELI CDD10-070

Feature		
Model		CDD10
Configuration No.		070
Type		Fork over
Mast type		Standard 2-Stage
Load capacity	kg	1000
Load center	mm	600
Wheel base	mm	1150
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
Dimension		
Standard lift height	mm	2000/2500/3000/3300
Max.extend height	mm	2385/2885/3385/3685
Mast lowered height	mm	1550/1800/2050/2200
Lowered fork height	mm	90
Fork size(length/width/thickness)	mm	1150(1220)/185/55
Overall length	mm	1733
Overall width	mm	790
Outside width between forks	mm	550/600/650/685
Inside width between forks	mm	180/230/280/315
Min.Turning radius	mm	1350
Min.Aisle width for pallets 800×1200	mm	1914
Min.Aisle width for pallets 1000×1200	mm	1955
Min.ground clearance	mm	30
Performance		
Travel speed,laden/unladen	km/h	3/3.5
Lift speed,laden/unladen	mm/s	130/230
Lowering speed,laden/unladen	mm/s	130/230
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor/Lift motor/Steering motor	kW	DC0.63/DC2.0
Battery voltage	V	24
Battery capacity	Ah	70
Brake		Electromagnetic/Regenerative
Controller		HELI(Options CURTIS)
Weight		
Battery weight	kg	48
Service weight with battery	kg	580

\* Details of specifications and equipment are based on information available at time of printing and may change without notice.



**ANHUI HELI INDUSTRIAL VEHICLE IMP. AND EXP. CO., LTD.**

ADD: 668 FANGXING ROAD, HEFEI, ANHUI, CHINA  
TEL : +8655163639068  
FAX : +8655163639966  
Email : heli@helichina.net  
WEBSITE : WWW.HELICHINA.COM / WWW.HELICHINA.NET